

The ECS120-S series are split-core current transformers. The CT can be mounted to existing panels, such as control centers or load centers, to measure or monitor wattage. These CTs can be mounted without removing existing cables for easier installation.



### Electrical Specifications

MODEL	INPUT CURRENT	AVAILABLE OUTPUT
ECS120-1000S	1000 A	CURRENT OUTPUTS @ 20mA, 40mA, 50mA, 100mA, 1A, 5A VOLTAGE OUTPUTS @ 0.25V, 0.33V, 0.5V, 1V, 2V (can be customized by customer)
ECS120-1200S	1200 A	
ECS120-1500S	1500 A	
ECS120-2000S	2000 A	
ECS120-2500S	2500 A	



### APPLICATIONS

- Energy and sub-metering products
- Electrical load monitoring
- Network equipment
- Instruments and sensors
- Control systems
- Go GREEN initiatives


### FEATURES

- 3.15\*4.72" window opening (ID)
- Custom design Turns-Ratio available
- Rigid housing case with UL 94V-0 durable plastic
- M4 terminal output
- Approximate weight 950g


### SPECIFICATIONS

- Standard Input Current 5-2500A
  - Frequency 50Hz — 400Hz
  - Standard accuracy 0.5, 1
  - Insulation Voltage 4000 Vac/1min
  - Operating Temp. -40°C to +30°C
  - Storage Temp. -45°C to +85 °C
  - ANSI C57.13 and IEC61869-2
- Standards

### Mechanical Dimensions in mm



### Connection Diagram



### CAUTION

Before installation, safety precautions must be followed by licensed professional. Never energize primary unless short circuited terminals or burden connected to secondary.